





## WIRELESS RECEIVERS

AZDEN's **330UPR Dual-Channel UHF Wireless Receiver** allows the user to operate two transmitters simultaneously. It features 188 user-selectable UHF frequencies (41 frequencies in the European version), high-gain antennas, a digital LCD display with multifunction readout, a 3.5mm (1/8" mini-jack) output and also a headphone output to monitor audio. Ideal for interviews and multiple on-camera subjects, the AZDEN 330UPR can be used in conjunction with any combination of belt-pack, plug-in or handheld style transmitters, giving the user plenty of flexibility. An AZDEN 330 Series Wireless System also includes an XLR adapter cable for use with higher-end cameras.

With the **310UDR UHF Wireless Diversity Receiver** you can be sure to get great audio just about anywhere. That's because AZDEN designed it with advanced diversity technology, utilizing two antennas to practically eliminate common signal integrity issues such as drop-outs and noise. It also features 188 user-selectable UHF frequencies (41 in the European version), digital LCD display with multifunction readout, a 3.5mm (1/8" mini-jack) output and headphone output to monitor audio. With a slightly smaller form factor, the 310UDR Receiver offers the same quality as the 330UPR and is operable with any of AZDEN's 3 transmitter types, but is meant for just a single on-camera subject. An AZDEN 310 Series Wireless System also includes an XLR adapter cable for use with higher-end cameras.

## WIRELESS TRANSMITTERS

The **35BT Body-Pack Transmitter** is the standard transmitter for the 330UPR and 310UDR receivers, and has the same flexibility and ease of use. With 188 selectable UHF frequencies (41 in the European version) and a multi-function LCD screen read-out, you'll always be sure to find a "free" channel. As part of a system the 35BT comes with a high-quality, omni-directional lavalier microphone with lock-down connector (EX-503L). Other features include a microphone input level control and audio standby switch.

For those who prefer to "bring your own microphone," AZDEN's **35XT Plug-In Transmitter** instantly makes any microphone with a 3-pin XLR output wirelessly compatible with a 330UPR or 310UDR receiver. With the same performance and feature set as the 35BT, you can depend on the 35XT to deliver quality audio. Compact yet lightweight, the 35XT also may be used as a body-pack transmitter with an XLR lavalier microphone. It features a locking-ring connector to make sure it attaches securely to your microphone.

With the same performance and functionality as the 35BT, the **35HT Handheld Transmitter** offers the user the convenience of a wireless transmitter and handheld microphone combined together. Both lightweight and durable, the 35HT is built to prevent "handling noise" and is equipped with a highly directional dynamic microphone element to isolate a subject's voice even in a noisy environment.

The **30HT-CE Handheld Transmitter** is specifically designed for use with European versions of the 330UPR and 310UDR receivers, which operate on 41 different UHF frequencies. Much like the 35HT, the 30HT-CE is lightweight, durable and is built to prevent "handling noise." A sensitive, uni-directional, electret condenser microphone element allows the microphone to be held at a comfortable distance away from a speaking subject's mouth.



## SPECIFICATIONS

### RECEIVERS

Freq. Range: UHF 188 Frequencies (566.125-589.875MHz)  
41 Frequencies for CE Versions (863.000-865.000MHz)  
Oscillator: PLL Synthesized  
RF Squelch Level: -95dBm  
Freq. Response: 50Hz – 15kHz  
S/N Ratio: >84dB (100% deviation)  
Mic Level Out: 3.5mm Mini Jack, -64dBm @±5kHz deviation  
Batteries: 2 "AA" Alkaline (2 x 1.5V) w/ 5-6 hours runtime

### 330UPR / 330UPR-CE

Receiver Type: Dual-Channel  
Dimensions: 2.87 x 4.45 x 1.59 inches (73 x 113 x 40.5 mm)  
Weight: Approx. 10.2 oz (290g) w/ batteries

### 310UDR / 310UDR-CE

Receiver Type: Single-Channel Diversity  
Dimensions: 2.48 x 3.86 x 1.12 inches (63 x 98 x 28.5 mm)  
Weight: Approx. 6.7oz (190g) w/ batteries

### TRANSMITTERS

Freq. Range: UHF 188 Frequencies (566.125-589.875MHz)  
41 Frequencies for CE Versions (863.000-865.000MHz)  
Oscillator: PLL Synthesized  
RF Power: 25mW  
Freq. Response: 50Hz – 15kHz  
Batteries: 2 "AA" Alkaline (2 x 1.5V) – 6-8 hours runtime

### 35BT / 35BT-CE

Max. Deviation: ±40kHz @ 1kHz Mod., Mic Input – 11dBm  
Dimensions: 2.52 x 3.93 x 1.16 inches (64 x 100 x 27 mm)  
Weight: Approx. 6oz (170g) w/ batteries

### 35HT (US Version Only)

Max Deviation: ±40kHz @ 1kHz Modulation  
Mic input: -65dBm (dev ± 5kHz)  
Mic Element: Uni-directional dynamic  
Dimensions: φ1.88 x 9.56 inches (φ48 x 234 mm)  
Weight: Approx. 9.6oz (270g) w/ batteries

### 30HT-CE

Antenna: 1/4 wavelength, internal  
Mic Element: Cardioid Electret Condenser  
Ref Deviation: ± 5 kHz (-60dBm - 1kHz input) ± 40kHz max dev  
Noise Reduction: Compander (TOKO)  
Dimensions: φ1.73 x 9.05 inches (φ44 x 230 mm)  
Weight: 4.6 oz (130g) w/ batteries

### 35XT (US Version Only)

Antenna: Internal  
Connection: Locking female 3-pin XLR  
Max Input level: -16dBm  
Input Impedance: 25k ohms  
Audio Adjust Range: -65dBm to 46dBm  
Dimensions: 1.57 x 1.57 x 4.49 inches (40 x 40 x 114 mm)  
Weight: Approx. 6.4oz (180g) w/ batteries

**FOR A FULL LIST OF AVAILABLE 310 & 330 SYSTEMS VISIT [WWW.AZDEN.COM](http://WWW.AZDEN.COM)**

