



Metz mecablitz 24 AF-1 digital



Weight without batteries: 125 g
Dimensions in mm (W x H x D): 65 x 98 x 54

24 AF-1 for Canon	No. 002431196
24 AF-1 for Nikon	No. 00243149A
24 AF-1 for Olympus / Panasonic	No. 002431290
24 AF-1 for Pentax	No. 002431793
24 AF-1 for Sony	No. 002431699

Flash output

- GN 24 with ISO 100/21° and 35 mm
- High number of flashes (e.g. 150 full flashes with alkaline magnesium batteries)
- Flash cycle time 0,3 – 5 sec. (depending on power supply and flash power)

Basic configuration

- Vertical tilting reflector +90°
- LED display
- Integrated autofocus measurement flash
- Flash readiness and exposure control indicators on the unit and camera (depending on camera)

Basic flash modes

- TTL flash mode
- 1st and 2nd shutter curtain synchronization (depending on camera)
- Automatic fill-in flash

Camera-specific flash modes

- E-TTL- flash mode (Canon)
- i-TTL- flash mode (Nikon)
- P-TTL- flash mode (Pentax)
- Four-Thirds-TTL- flash mode (Olympus / Panasonic / Leica)
- ADI- flash mode (Sony)

Guaranteed in the future

- Firmware update possible via Metz service

Power supply

- 2 x AA alkaline magnesium batteries
- 2 x AA NiCad or NiMH batteries

Included in delivery

- Instruction manual